



PO Box 1581
Appleton, WI 54912

Phone (800)-434-3750
Fax (800)-434-3751

Acoustic Ceiling Products

Classic X Stab Ceiling System

Product Data

Material: Minimum G40 Hot Dipped Galvanized Steel

Surface Finish: Baked Polyester Paint over Hot Dipped Galvanized Steel or Aluminum

Profile: Double Web Exposed Tee

Face Dimensions: 15/16"

End Detail: High tensile staked-on stab

ASTM Classification: Heavy Duty and Intermediate Duty in accordance with ASTM C 635 (Standard Specification for the Manufacture, Performance, and Testing of Metal Suspension Systems for Acoustical Tile and Lay-in Panel Ceilings).

Fire Performance: 3 Hour Fire Rating as tested in accordance with ASTM E 119 (Standard Test Methods for Fire Tests of Building Construction and Materials).

Seismic Zone: Zones 0 - 4

Seismic Performance: Compression/Tension - Exceeds 180 lbs. to pull out both main runners and cross tees. In accordance with ASTM E 580 (Standard Practice for Application of Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels in Areas Requiring Seismic Restraint).

Installation: Recommended to install in accordance with ASTM C 636 (Standard Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels).

Warranty: 25 Year Limited Warranty